

## TED TODD

## SPECIFICATION SHEET

## CALICO WIDE PLANK

Item code: PROJ013 Collection: Project

| Overview                    |   |  |
|-----------------------------|---|--|
| Wood Species                | European Oak  |  |
| Design                      | Plank   |  |
| Grade                       | Nature  |  |
| Profile                     | Tongue & grooved to all sides   |  |
| Edge Detail                 | Micro bevelled  |  |
| Construction                | 3 Layer Engineered  |  |
| Wear Layer                  | 3mm Hardwood (Nominal)  |  |
| Application Guide           | Floors, walls & ceilings  |  |
| Dimensions                  |   |  |
| Width                       | 190mm   |  |
| Thickness                   | 14mm  |  |
| Length                      | Up to 1.90m (Random)  |  |
| Tolerance                   | +/- 0.50mm / 95% in tolerance   |  |
| Pack Size, M2               | 2.888 m2 - order to the nearest pack size                               |  |
| Finish                      |   |  |
| Finish                      | Hardened Oil  |  |
| Surface Texture             | Medium brushed  |  |
| Tone                        | Light Tone  |  |
| Tonal Variation             | Medium natural tonal variation  |  |
| Batch Variation             | Not advised to mix batches in one floor area                            |  |
| Handover guidance           | Fully finished, ready for use.  |  |
| Floor Care                  | Care System 3   |  |
| Environmental Certification |   |  |
| Certification               | FSC 100% - independently audited, since 1997, chain of custody tracking |  |
| UKTR Compliant              | Yes   |  |
| Installation Guidelines     |   |  |
| Floating Installation       | Yes - Ted Todd - range of underlays                                     |  |
| Secret Nail                 | Not recommended   |  |
| Structural Floor            | No  |  |



| Fully Bond                               | Yes - Ted Todd MS Flex high strength adhesive                           |  |
|--|---|--|
| Sub floor Primer                         | Yes - Ted Todd Primerfast   |  |
| Underfloor Heating                       | Yes - please see usage guidelines                                       |  |
| Sub Floors                               |   |  |
| Concrete                                 | Dry, Flat   |  |
| Plywood                                  | Yes   |  |
| Screed                                   | Dry, flat, with Primerfast moisture barrier                             |  |
| Formed Tread +<br>Riser                  | Yes - Made to order - 14 day service                                    |  |
| L Section, T Section,<br>Reducer, Scotia | Yes - 7 day service   |  |
| Skirting, Architrave                     | Yes by request  |  |
| Technical Information                    |   |  |
| Moisture Content                         | 8-12% fair and average moisure content                                  |  |
| Slip Rating                              | Low risk dry. Low risk wet.   |  |
| EN 13501-1 Fire<br>Rating Flooring       | Efl   |  |
| EN 14342 Emissions                       | E1  |  |
| Humidity<br>requirements                 | Between 40 and 60% relative humidity                                    |  |
| Origin                                   | European  |  |
| Janka Hardness<br>Rating                 | 1,120 lbf (4980N)   |  |
| Formaldehyde<br>Emission                 | E1  |  |
| Thermal Conductivity                     | 15mm 0.08m2K/W, 0.8 Tog   |  |
| Shipping Information                     |   |  |
| Shipment times                           | Largest UK Stocks - available 3 day service                             |  |
| Packaging                                | Palletised, wrapped + banded  |  |
| Guarantee                                |   |  |
| Warranty                                 | 30 year product warranty  |  |
| Life Cycle                               |   |  |
| Life Span                                | Generational life span if cared for                                     |  |
| Recycle                                  | Value in recycling into upscale uses, worst case outcome carbon neutral |  |
| Reuse                                    | Reclaim and re-use as flooring  |  |





18 Chesford Grange, Woolston, Warrington, Cheshire, WA1 4RQ | Tel: 01925 283000 | Fax: 01925 283001 | www.tedtodd.co.uk | Company Registration No: 2848796 | VAT Registration No: 719682205