



TED TODD

SPECIFICATION SHEET

LINTON WIDE PLANK

Item code: PROJ030

Collection: Project



| Overview | | | |
|-----------------------------|---|---------------------------------------|---|
| Wood Species | European Oak | Fully Bond | Yes - Ted Todd MS Flex high strength adhesive |
| Design | Plank | Sub floor Primer | Yes - Ted Todd Primerfast |
| Grade | Nature | Underfloor Heating | Yes - please see usage guidelines |
| Profile | Tongue & grooved to all sides | Sub Floors | |
| Edge Detail | Micro bevelled | Concrete | Dry, Flat |
| Construction | 3 Layer Engineered | Plywood | Yes |
| Wear Layer | 3mm Hardwood (Nominal) | Screed | Dry, flat, with Primerfast moisture barrier |
| Application Guide | Floors, walls & ceilings | Formed Tread + Riser | Yes - Made to order - 14 day service |
| Dimensions | | L Section, T Section, Reducer, Scotia | Yes - 7 day service |
| Width | 190mm | Skirting, Architrave | Yes by request |
| Thickness | 14mm | Technical Information | |
| Length | Up to 1.90m (Random) | Moisture Content | 8-12% fair and average moisture content |
| Tolerance | +/- 0.50mm / 95% in tolerance | Slip Rating | Low risk dry. Low risk wet. |
| Pack Size, M2 | 2.888 m2 - order to the nearest pack size | EN 13501-1 Fire Rating Flooring | Efl |
| Finish | | EN 14342 Emissions | E1 |
| Finish | Absolute Matt | Humidity requirements | Between 40 and 60% relative humidity |
| Surface Texture | Medium brushed | Origin | European |
| Tonal Variation | Medium natural tonal variation | Janka Hardness Rating | 1,120 lbf (4980N) |
| Batch Variation | Not advised to mix batches in one floor area | Formaldehyde Emission | E1 |
| Handover guidance | Fully finished, ready for use. | Thermal Conductivity | 15mm 0.08m2K/W, 0.8 Tog |
| Floor Care | Care System 1 | Shipping Information | |
| Environmental Certification | | Shipment times | Largest UK Stocks - available 3 day service |
| Certification | FSC 100% - independently audited, since 1997, chain of custody tracking | Packaging | Palletised, wrapped + banded |
| UKTR Compliant | Yes | Guarantee | |
| Installation Guidelines | | Guarantee | 30 year product warranty |
| Floating Installation | Yes - Ted Todd - range of underlays | Life Cycle | |
| Secret Nail | Not recommended | Life Span | Generational life span if cared for |
| Structural Floor | No | Recycle | Value in recycling into upscale uses, worst case outcome carbon neutral |
| | | Reuse | Reclaim and re-use as flooring |



18 Chesford Grange, Woolston, Warrington, Cheshire, WA1 4RQ | Tel: 01925 283000 | Fax: 01925 283001 | www.tedtodd.co.uk

| Company Registration No: 2848796 | VAT Registration No: 719682205

