

























	Standard	Result
 Size		1211.2 mm x 169.8 mm
 Thickness	ISO 24346	4.5 mm
 Wear layer	ISO 24340	0.3 mm
Locking mechanism¹		2G™ angling installation system
Surface treatment		K-Guard+ PU coating
Guarantee²	Residential	20 years
 Bevelled edge		No
 Mass per unit area	ISO 23997	6575 g/m ²
 Standards	EN 16511	Pass (Multilayer modular floorcovering panels)
 Classification	ISO 10874 - Domestic	23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN 438-2	Pass (Grade 5)
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN 13329 Annex E	Pass (>1200 cycles)
 Furniture chair leg	EN 424	Pass (No visible damage)
 Dimensional stability	BS EN ISO 23999	Pass (< 0.25%)
 Swelling	ISO 24336	Pass (0.2%)
 Acoustic impact noise reduction	EN ISO 10140-1:2016	ΔL _w = 19 dB
 Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
 Impact resistance	EN 13329 Annex F	Pass (> 1800 mm)
 Thermal resistance	ISO 8302	0.052 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance³	EN 13893 DIN 51130	DS R9
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Adhesive		None required, Please install according to our installation instructions.
 Environmental	Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 ISO 14001 / ISO 9001	Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. Manufactured to quality and environment management systems standard
 Recycling		Suitable
 Phthalate free		Yes

¹ 2G™ is a patented technology invented by Välinge Innovation AB. The 2G™ word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

² Subject to terms. Please see our website.

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:
Call: 01386 820210
Email: info@palioexpress.com
Visit: www.palioexpress.com



EN 14041: 2004 (DOP 2020/PRC/EN/01)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23 Manufactured to EN 16511



BS EN 14041: 2004 (DOP 2021/UKCA/PRC/01)
Approved body 0321 Floor coverings (internal)
ISO 10874 Class 23 Manufactured to EN 16511



Product Code	Size		Box Quantity		Slip Resistance	LRV
	mm	inches	m ²	Pieces	DIN 51130	
PVP142-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	26
PVP143-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	20
PVP144-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	34
PVP145-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	27
PVP146-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	27
PVP147-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	38
PVP148-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	21
PVP149-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	46
PVP150-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	25
PVP152-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	35
PVP153-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	32
PVP156-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	34
PVP157-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	42
PVP161-SCB	1211.2 x 169.8	47.69" x 6.69"	2.468	12 Planks	R9	52

Wood Designs